

# STAINLESS STEEL CABLE TIES SELF-LOCKING - SST SERIES

- INDOOR, OUTDOOR AND UNDERGROUND/DIRECT BURIAL APPLICATIONS
- PROVIDES A STRONG AND DURABLE METHOD OF BUNDLING AND FASTENING
- AVAILABLE IN AISI 304 OR AISI 316 (SUPERIOR CORROSIVE RESISTANCE)
- ABS, DNV-GL, LR AND BV APPROVED



PART NUMBER	LENGTH		WIDTH		MAX. BUNDLE DIA.		TENSILE STRENGTH		QTY (PCS/BAG)
	IN.	MM	IN.	MM	IN.	MM	LBS	KGS	

#### Standard Cross Section

TISS-SST125	4.9	125	0.18	4.6	1.37	35	100	45.4	100
TISS-SST150	6.0	150	0.18	4.6	1.70	44	100	45.4	100
TISS-SST200	8.0	200	0.18	4.6	2.00	50	100	45.4	100
TISS-SST360	14.2	360	0.18	4.6	4.00	102	100	45.4	100
TISS-SST520	20.4	520	0.18	4.6	6.00	152	100	45.4	100
TISS-SST680	26.8	680	0.18	4.6	8.00	203	100	45.4	100
TISS-SST840	33.0	840	0.18	4.6	10.00	254	100	45.4	100
TISS-SST1000	41.3	1050	0.18	4.6	12.50	318	100	45.4	100

#### Heavy Cross Section

TISS-SST150HD	6.0	150	0.31	7.9	1.70	44	250	113.4	50
TISS-SST200HD	8.0	200	0.31	7.9	2.00	50	250	113.4	50
TISS-SST360HD	14.2	360	0.31	7.9	4.00	102	250	113.4	50
TISS-SST520HD	20.4	520	0.31	7.9	6.00	152	250	113.4	50
TISS-SST680HD	26.8	680	0.31	7.9	8.00	203	250	113.4	50
TISS-SST840HD	33.0	840	0.31	7.9	10.00	254	250	113.4	50
TISS-SST1000HD	41.3	1050	0.31	7.9	12.50	318	250	113.4	50

#### Extended Heavy Cross Section

TISS-SST200EHD	8.0	200	0.51	13.0	2.00	50	500	227	50
TISS-SST360EHD	14.2	360	0.51	13.0	4.00	102	500	227	50
TISS-SST520EHD	20.4	520	0.51	13.0	6.00	152	500	227	50
TISS-SST680EHD	26.8	680	0.51	13.0	8.00	203	500	227	50
TISS-SST840EHD	33.0	840	0.51	13.0	10.00	254	500	227	50
TISS-SST1000EHD	41.3	1050	0.51	13.0	12.50	318	500	227	50

#### Super Heavy Cross Section

TISS-SST200PD	8.0	200	0.625	16.0	2.00	50	500	227	50
TISS-SST360PD	14.2	360	0.625	16.0	4.00	102	500	227	50
TISS-SST520PD	20.4	520	0.625	16.0	6.00	152	500	227	50
TISS-SST680PD	26.8	680	0.625	16.0	8.00	203	500	227	50
TISS-SST840PD	33.0	840	0.625	16.0	10.00	254	500	227	50
TISS-SST1000PD	41.3	1050	0.625	16.0	12.50	318	500	227	50

# STAINLESS STEEL CABLE TIES

## SELF-LOCKING FULLY COATED - STFC SERIES

- FULLY COATED EPOXY, AVAILABLE IN NYLON COATED UPON REQUEST
- PROVIDES EXCELLENT RESISTANCE TO CHEMICAL AND SALT-SPRAY
- UV RESISTANT, FLAME RETARDANT AND HALOGEN FREE MATERIAL
- AVAILABLE IN AISI 304 OR 316 (SUPERIOR CORROSIVE RESISTANCE)
- ABS, DNV-GL, LR AND BV APPROVED



PART NUMBER	LENGTH		WIDTH		MAX. BUNDLE DIA.		TENSILE STRENGTH		QTY (PCS/BAG)
	IN.	MM	IN.	MM	IN.	MM	LBS	KGS	

### Standard Cross Section

TISSFC-STFC125	4.9	125	0.18	4.6	1.37	35	100	45.4	100
TISSFC-STFC150	6.0	150	0.18	4.6	1.70	44	100	45.4	100
TISSFC-STFC200	8.0	200	0.18	4.6	2.00	50	100	45.4	100
TISSFC-STFC360	14.2	360	0.18	4.6	4.00	102	100	45.4	100
TISSFC-STFC520	20.4	520	0.18	4.6	6.00	152	100	45.4	100
TISSFC-STFC680	26.8	680	0.18	4.6	8.00	203	100	45.4	100
TISSFC-STFC840	33.0	840	0.18	4.6	10.00	254	100	45.4	100
TISSFC-STFC1000	41.3	1050	0.18	4.6	12.50	318	100	45.4	100

### Heavy Cross Section

TISSFC-STFC150HD	6.0	150	0.31	7.9	1.70	44	250	113.4	50
TISSFC-STFC200HD	8.0	200	0.31	7.9	2.00	50	250	113.4	50
TISSFC-STFC360HD	14.2	360	0.31	7.9	4.00	102	250	113.4	50
TISSFC-STFC520HD	20.4	520	0.31	7.9	6.00	152	250	113.4	50
TISSFC-STFC680HD	26.8	680	0.31	7.9	8.00	203	250	113.4	50
TISSFC-STFC840HD	33.0	840	0.31	7.9	10.00	254	250	113.4	50
TISSFC-STFC1000HD	41.3	1050	0.31	7.9	12.50	318	250	113.4	50

### Extended Heavy Cross Section

TISSFC-STFC200EHD	8.0	200	0.51	13.0	2.00	50	500	227	50
TISSFC-STFC360EHD	14.2	360	0.51	13.0	4.00	102	500	227	50
TISSFC-STFC520EHD	20.4	520	0.51	13.0	6.00	152	500	227	50
TISSFC-STFC680EHD	26.8	680	0.51	13.0	8.00	203	500	227	50
TISSFC-STFC840EHD	33.0	840	0.51	13.0	10.00	254	500	227	50
TISSFC-STFC1000EHD	41.3	1050	0.51	13.0	12.50	318	500	227	50

### Super Heavy Cross Section

TISSFC-STFC200EXD	8.0	200	0.625	16.0	2.00	50	500	227	50
TISSFC-STFC360EXD	14.2	360	0.625	16.0	4.00	102	500	227	50
TISSFC-STFC520EXD	20.4	520	0.625	16.0	6.00	152	500	227	50
TISSFC-STFC680EXD	26.8	680	0.625	16.0	8.00	203	500	227	50
TISSFC-STFC840EXD	33.0	840	0.625	16.0	10.00	254	500	227	50
TISSFC-STFC1000EXD	41.3	1050	0.625	16.0	12.50	318	500	227	50